



# Roll Clamps

Roll Clamp with a short fixed arm and a long complete one. 90° frontal tipping allows the gripping of the rolls, placed perpendicular to the axis of the forklift. A wide choice of openings, capacities and contact pads allow to find the perfect attachment for every needs.

## 343SF ROLL CLAMP WITH 90° FORWARD TIPPING AND SHORT FIXED ARM

REFERENCE	ATTACHMENT CAPACITY Kg	ISO 2328 FEM	ROLLS DIAMETER		CONTACT PADS (DxL) mm	THICKNESS (S) mm	CENTER OF GRAVITY (CG) mm	CENTER OF GRAVITY (CG1) mm	WEIGHT (Q) Kg
			(J) mm	(K) mm					
21K002G2C0001	900	II	350	1100	700X200	235	215	320	510
21K002G2C0002	900	II	350	1400	700X200	235	220	340	560
21K002Q2C0001	1300	II	400	1150	750X250	235	235	360	590
21K002Q2C0002	1300	II	400	1300	750X250	235	240	370	615
21K00342C0001	2000	II	400	1300	850X250	250	250	400	730
21K00343C0001	2000	III	400	1300	850X250	265	250	400	800
21K00343C0002	2000	III	400	1600	850X250	265	255	420	850
21K003G3C0001	2600	III	550	1300	900X250	300	260	430	990
21K003G3C0002	2600	III	750	1600	900X250	300	270	460	1040
21K003Q3C0001	3000	III	400	1300	1015X300	310	275	455	1070
21K003W4C0001	3600	IV	750	1800	1050X300	320	280	505	1495

Hydraulic functions required: 2 | Maximum working pressure: 175 bar



### OPTIONS

- Pipes and Fitting Kit.
- Quick Release Hoses couplings Kit.
- Pressure Gauge.
- Quick Release Hooks.
- Solenoid Valve two Functions with Electric Kit (specify voltage).
- Pressure Relief Valve, Non-Return Valve, Regenerative Valve.
- 3 Position Pressure Relief Valve.
- Manual Pressure-Relief Panel with Pressure Gauge and Indicator Lamp.
- Electronic Pressure-Relief Panel with Keyboard and Indicator Lamp.
- Automatic Pressure-Relief System.
- Semi-Integral Sideshift.
- Automatic Greasing System for Semi-Integral Sideshift.

- Mechanical block of Rotation at 180°.
- Milled Contact Plates/Coated Plates with a corundum layer (on request).
- Contact Plates with standard Rubber Coating.
- Contact Plates with smooth Rubber Coating.
- Contact Plates with honeycomb Rubber Coating

### ADDITIONAL EQUIPMENT ON REQUEST

- Roll and Tyres Clamps with special width and/or stroke.
- Roll and Tyres Clamps with parallel arms (ideal for containers loading/unloading operations, due to the clamp small size). Available both in the rotating and in the fixed versions.

### OIL FLOW RATE

In **bold** the values referred to the functions capacities, which are different from the clamping.

TYPE	ISO 2328 - FEM	MIN CAPACITY (L/min)	MAX CAPACITY (L/min)	RECOMMENDED CAPACITY (L/min)
343 SF	ISO 2	20/15	40/40	25/20
343 SF	ISO 3	22/15	40/40	30/20
343 SF	ISO 4	30/15	50/60	35/25

